OPERATOR QUOTATION FORM (Rev. 07/2024)

CLIENT:		Full company name:				lift components	
ORDER DA	ATE:						
ORDER REFER	RENCE:						
REQUESTED DI	ELIVERY:						
GENERAL INSTALLATION DATA							
DOOR CLEAR OPENING WIDTH:					600	<u> </u>	
					700	750	
					800	850	
					900	1000	
					1100	1200	
					1300		
SPECIFY MAXIMUM SHAFT SIZE:							
				PALLADIUM			
OPERATOR TYPE:				☐ LEONIDA			
				☐ INFINITY			
MODEL (TYPE)		Fixed cam			Without cam		
MODEL (11	:L (IYPE)	Retractable cam			Fixed cam with off	-floor door lock	
		Retractable cam with o	ff-floo	or door lock			
OPERATOR WITH LANDING VIEW OPENING: SUSPENSION TYPE: MANUAL OPENING VIEW FROM LANDING							
OPERATOR WITH LANDING VIEW OPENING:					SUSPENSION TYPE: MANUAL C	DPENING VIEW FROM LANDING	
						Opening LEFT	
					Opening RIGHT		
					$\begin{array}{ c c c c c c c c c c c c c c c c c c c$	Opening CENTRAL	
						Opening LEFT	
SF	FOR CENTRAL OPERATOR SPECIFY CAM POSITION FROM					Opening RIGHT	
LAND		DING VIEW:				Opening LEFT	
						Opening RIGHT	
REQUIRED ELECTRONIC BOARD:				☐ OP 105-N (power supply 24v-48v) ☐ OPR 501 (power supply 220v)			
			-	☐ Keypad			
			\longrightarrow	Elvi Motor 30			
MOTOR:			-	Enhanced Elvi Motor (102.754/FEE)			
			\longrightarrow	☐ 45 (SLIM) ☐ 45 (CENTRAL)			
CABIN THRESHOLD WIDTH:			+	믐	75	☐ 45 (CENTRAL)	
			-	<u> </u>	115	☐ 135	
ADDITIONAL CURRILIES				$\frac{\sqcup}{\sqcap}$	Threshold Profile	Apron	
ADDITIONAL SUPPLIES:				믐	Cover Profile	☐ Threshold Support	
			-	屵			
				Track pair for operator mounting on cabin roof (IL.912.0808)			
NOTES:							